BRADY.



Quick, Legible, Lab Labels.

A better way to identify your samples.

The LAB PAL $^{\scriptscriptstyle \rm M}$ label printer is portable, easy-to-use and makes identifying your samples more quick and efficient.

- Portable/Handheld
- Easy to use
- Labels withstand extreme lab conditions
- Pre-programmed vial and slide sizes
- Time/Date stamp
- Laboratory symbols
- Affordable–every tech needs one
- Banner mode for general labeling
- Serialization feature makes you more efficient



Pre-programmed vial ID sizes (0.6, 1.5 & 2 ml)



Date/Time stamp



Specific laboratory symbols

Long-lasting labels that stick... and stay stuck!

Æ

Zo

Brady's laboratory labels are designed to withstand extreme laboratory environments

- Liquid Nitrogen
- Hot Water Baths
- ► Freezers
- Autoclave

Brady's labels resist most chemicals

- Xylene
- AlcoholDMSO
- Ethanol





Take away the guesswork! Always be certain with LAB PAL.

Ask your distributor for a free demo, or learn more by visiting our website at <u>www.bradylabid.com</u>

Other Features

- Quick "drop-in" cartridge loading
- Multiple line printing
- 5 font sizes: (7, 10, 14, 20 & 28 pt)

Specifications

- Built-in cutter
- Automatic shut-off
- 6 month warranty (extended to 12 months with user registration)



Exposed edge makes peeling easy-even with gloves.

Drinter and



Colored tapes for general purpose labeling.

General Identification

Pre-cut labels for PCR tubes, vial tops and

Easy to serialize or print multiple labels -

Prints code 3 of 9 bar codes (also prints 128

and UPC bar codes when connected to a PC)

PC compatible (using LabelMark[™] software)

Self-Lam (wrap around labels) with a clear

every shape and size for the lab

window to check fluid levels

Print method:	Thermal transfer (durable, non-smearing)
Weight:	1.2 lbs. (0.55 kg) with batteries and tape cartridge included
Dimensions (L x W x H):	9.0 x 4.5 x 2.5 inches (228.6 x 114.3 x 63.5 mm)
Power source:	6 AA-size batteries or AC with optional adapter
Operating temperature:	40° - 120° F (4° - 49° C)
Agency Approvals:	Printer: FCC Class A approved
	Tapes: UL and CSA approved

Printer and Accessories				
umber Description				
LAB PAL label printer (includes PAL-375-461 label cartridge)				
AC adapter				
Hard-sided carry case				

Brady LAB PAL Label Printer Applications Chart							
Application	Material	Label V					
		3/8" / 9.5 mm	1/2" / 12.7 mm	3/4" / 19.1 mm	*Application Key		
	Polyester B461 / White*	PAL-375-461	PAL-500-461	PAL-750-461	Freezer (-70°C)		
	Nylon Cloth B499 / White	PAL-375-499	PAL-500-499	PAL-750-499	N Liquid Nitrogen (-196°C)		
	Polyester B488 / White	PAL-375-488	PAL-500-488	PAL-750-488	Autoclave		
9 4 9 6	Polyester B423 / White	PAL-375-423	PAL-500-423	PAL-750-423	Hot Water Baths (100°C)		
9 0	Polyester B430 / Clear	PAL-375-430	PAL-500-430	PAL-750-430	Low-Profile (extremely thin)		
99	Vinyl B439 / White**	PAL-375-439	PAL-500-439	PAL-750-439	Vial Identification Slide Identification		
* B461 is acceptable for use in lig	uid nitrogen only when wrapped upon its	elf. as in self-lamination.			Plate Identification		

B461 is acceptable for use in liquid nitrogen only when wrapped upon itself, as in self-lamination.

** B439 vinyl is available in blue, green, orange, red and yellow.

Section of the sectio -

Need the most powerful portable printer? Check out the LAB PAL's big brother – the TLS2200[®] Portable Labeling System.

Brady offers the ultimate answer to your lab's toughest labeling challenges. The easy to use TLS2200 labeling system is a light weight (2.75 lb./1.25 kg) portable printer that provides capabilities such as thermal transfer printing, bar coding and multiple material configurations. Printing labels for vials, vial tops, test tubes, well plates, beakers and slides is faster and easier than ever before.

Catalog Number

TLS2200

Description

Printer (system includes hard case, R6210 ribbon, battery pack, battery charger, Quick Start Guide, manual, communications cable, test labels (PTL-19-423), one cleaning card.)

ideal for aliquots

www.bradylabid.com



Tel.1-800-895-8080 ext. 6614 6555 West Good Hope Road Milwaukee, WI 53201 Y355387 All Rights Reserved © 2003 USA Brady Corporation